

Stirring — 5" Led Digital Magnetic Stirrer

FEATURES

- Digital process timer allows for unsupervised operation and can be set from 1min to 99h59min
- Stainless Steel with ceramic coated working plate is chemical-resistant and scratch-resistant
- Brushless DC motor is maintenance-free and explosion-proof
- 3D digital wheel adjustment of speed and temperature
- LED digital display for easy setting and reading
- Speed range is 50-1500rpm



SPECIFICATIONS

Model	MI0102008
Stirring positions	1
Set-up plate dimensions [mm]	Ø 137
Set-up plate material	Stainless Steel with ceramic coated
Motor type	Brushless DC motor
Max. stirring quantity [H ₂ O, L]	20
Max. stirring bar [L x Φ, mm]	55*10
Motor rating input [W]	30
Motor rating output [W]	20
Speed range [rpm]	50-1500
Speed display	LED
Time display	LED
Time range	1min - 99h59min
Permissible ambient temperature [°C]	5-40
Permissible relative humidity	80%
Protection class according to DIN EN 60529	IP 42
Voltage [VAC]	200-240/100-120
Frequency [Hz]	50/60
Power [W]	40
Dimensions [W x D x H, mm]	250 x 148 x 85
Weight [kg]	1.7