

Water distillation apparatus

Biostill 4 | Biostill 10

Ideal for:

- all water distillation processes

Features:

- fully automatic operation
- borosilicate glass 3.3
- ideal for high purity water
- free of pyrogen and metal ions
- safety features allow unattended operation



Biostill 10



Biostill 4

| Model | Biostill 4 | Biostill 10 |
|--|---|----------------------------|
| Distilled water production | 4.3 l/h | 10 l/h |
| pH | | 5.5 - 7 |
| Water consumption | 1 l/min | 2 l/min |
| Conductivity at 20°C | 1 µS/cm* | 1.5 µS/cm* |
| Dimensions (W x D x H), weight | 400 x 590 x 170 mm, 5.2 kg | 960 x 360 x 400 mm, 23 kg |
| Packing size (W x D x H), gross weight | 520 x 310 x 610 mm, 9.5kg | 1130 x 610 x 770 mm, 30 kg |
| Power supply | 1 Phase AC 120V, 60 Hz or AC 230V, 50/60 Hz | |
| Order number 230V | 2 190 104 | 2 190 110 01 |

*As distillates are open to the atmosphere before measurements can be made, the value of conductivity is really much less (down to 10 times) than it is really measured. Any ultra pure water in contact with the atmosphere has a conductivity of 1-2 µS/cm and a pH of 5, due to the small amount of CO₂ (0.5 ppm) absorbed from the atmosphere.