

## -40°C Freezer



268L



328L



528L

### Technical Parameters

| Model                | BDF-40V268   | BDF-40V328          | BDF-40V528                     |
|----------------------|--|---------------------|--------------------------------|
| External Size(W*D*H) | 673*676*1630mm   | 673*676*1860mm      | 900*819*1828mm                 |
| Internal Size(W*D*H) | 508*455*1137mm   | 508*455*1393mm      | 651*631*635mm<br>651*631*635mm |
| Capacity             | 268L   | 328L                | 528L                           |
| Type                 | Vertical   |                     |                                |
| Temp. Range          | -30°C~-40°C  |                     | -20~-40°C                      |
| Temp. Accuracy       | 0.1°C  |                     |                                |
| Control System       | Microprocessor Control<br>LED Display  |                     |                                |
| Alarm                | High or low temperature alarm,power failure alarm,door ajar alarm,sensor failure alarm<br>(only for BDF-40V268&BDF-40V328),temperature controllers failure alarm |                     |                                |
| Refrigeration Type   | Direct Refrigeration   |                     |                                |
| Refrigerant          | R290   |                     |                                |
| Compressor           | Unicompressor,imported famous brand compressor   |                     |                                |
| Structure            | Unibody design   |                     |                                |
| Material             | Internal   | Color sprayed steel |                                |
|                      | External   | Color sprayed steel |                                |
| Drawer/Shelf         | 3pcs shelves   | 3pcs shelves        | 18 drawers                     |
| Consumption          | 300W   |                     | 345W                           |
| Power Supply         | AC220V±10%, 50/60HZ; 110V, 60Hz  |                     |                                |
| Package Size         | 760*770*1800mm   | 770*770*2040mm      | 930*970*2000mm                 |
| Gross Weight         | 115kg  | 131kg               | 184kg                          |



268L/362L



398L

## Technical Parameters

| Model                | BDF-40V268II   | BDF-40V362                                   | BDF-40V398  |
|----------------------|--|--|---|
| External Size(W*D*H) | 690*744*1631mm   | 690*744*1885mm                               | 850*960*1860mm                                      |
| Internal Size(W*D*H) | 520*567*1013mm   | 520*567*1266mm                               | 550*630*1140mm                                      |
| Capacity             | 268L   | 362L   | 398L  |
| Type                 | Vertical   |  |   |
| Temp. Range          | -30℃~-40℃  |  | -15~-40℃  |
| Temp. Accuracy       | 0.1℃   |  |   |
| Control System       | Microprocessor Control; Digital Display  |  |   |
| Alarm                | High or low temperature alarm,door ajar alarm,power failure alarm,temperature controller failure alarm |  | High or low temperature alarm, sensor failure alarm |
| Refrigeration Type   | Direct Refrigeration   |  |   |
| Refrigerant          | Mixed refrigerant  |  |   |
| Compressor           | Unicompressor,imported famous brand compressor   |  |   |
| Construction         | Structure  | Uniboday design                              |   |
|                      | Internal Material  | Stainless steel                              |   |
|                      | External Material  | Painted steel panel,110mm foaming insulation | Painted steel panel,150mm foaming insulation        |
| Drawer/Shelf         | 4pcs shelves,Stainless Steel   | 5pcs shelves,Stainless Steel                 | 3pcs shelves,Stainless Steel                        |
| Consumption          | 335W   | 360W   | 550W  |
| Power Supply         | AC220V±10%,50/60HZ;110V,60Hz   |  |   |
| Package Size         | 810*860*1820mm   | 810*860*2100mm                               | 935*1030*2030mm                                     |
| Gross Weight         | 165kg  | 180kg  | 250kg   |