


**ATTENTION: LOW PARALLELISM OF TWO MEASURING FACES**

- Measure root tangent length of gear
- Graduation 0.01mm
- Ratchet stop
- Supplied with setting standards





Code	Range	Accuracy	Parallelism	L	b	c
<b>3282-25</b>	0-25mm	4µm	5µm	34	24	3.3
<b>3282-50</b>	25-50mm	4µm	5µm	59	32	3.3
<b>3282-75</b>	50-75mm	5µm	5µm	85	45	3.3
<b>3282-100</b>	75-100mm	5µm	5µm	110	57	3.3

## DISK MICROMETERS (ECONOMIC TYPE)



**3282-25**




Unit: mm

**ATTENTION: LOW PARALLELISM OF TWO MEASURING FACES**

**NON-ROTATING SPINDLE**

- Measure root tangent length of gear
- Graduation 0.01mm
- Non-rotating spindle
- Ratchet stop
- Supplied with setting standards





Code	Range	Accuracy	Parallelism	L	b
<b>3294-25</b>	0-25mm	4µm	5µm	34	24
<b>3294-50</b>	25-50mm	4µm	5µm	59	32
<b>3294-75</b>	50-75mm	5µm	5µm	85	45
<b>3294-100</b>	75-100mm	5µm	5µm	110	57

## NON-ROTATING SPINDLE DISK MICROMETERS (ECONOMIC TYPE)



**3294-25**



Unit: mm

## DIGITAL NON-ROTATING SPINDLE DISK MICROMETERS (ECONOMIC TYPE)

ATTENTION: LOW PARALLELISM OF TWO MEASURING FACES

DATA OUTPUT


NON-ROTATING SPINDLE

5

- Measure root tangent length of gear
- Resolution 0.001mm/0.00005"
- Non-rotating spindle
- Button function: on/off, set, mm/inch, ABS/INC
- Data output
- LR44 battery, automatic power off
- Ratchet stop
- Supplied with setting standards
- Optional accessory: data output cable (code 7315-30, 7302-30)



3594-25A



Code	Range	Accuracy	Parallelism	L	b
3594-25A	0-25mm/0-1"	±4μm	5μm	43mm	32mm
3594-50A	25-50mm/1-2"	±4μm	5μm	68mm	44.5mm
3594-75A	50-75mm/2-3"	±5μm	5μm	93mm	57mm
3594-100A	75-100mm/3-4"	±5μm	5μm	118.5mm	70mm

