



# LABTEX

## Data Loggers




# SMS Alarm Data Logger

## GSM-10E / GSM-11E / GSM-20E / GSM-21E

These data loggers can be used to measure and store readings of humidity and temperature automatically. The device is with a large LCD which can display real-time readings and logging indication. These data loggers can send SMS alarm messages to the authorized user if the humidity and temperature exceed the limits of the setting. User can also dial the data logger through any mobile phone to get the readings of humidity and temperature.

User can set up and download the recorded data through the software easily by connecting the device to PC via USB. Then user can view and analyse the data, or export files in different formats(txt, xls, csv, bmp, jpg).



- Waterproof external probe and its length can be customized
- Over-limit alarm settings for all channels
- Two points calibration for each channel
- Replaceable battery and data anti-lost when power off
- Start logging: Immediately, Button, Start at
- Professional PC software: DGraph
- Connect the device with with PC to set up and download data
- Precise and low cost

## SPECIFICATIONS

		GSM-10E	GSM-11E	GSM-20E	GSM-21E
Relative humidity	Measuring range			0~100%RH	0~100%RH
	Accuracy			±3%RH(20~80%RH,25°C) ±5%(others)	±2%RH(20~80%RH,25°C) ±3%(others)
	Resolution			0.1%RH	0.1%RH
Temperature	Measuring range	-40 to 125°C (-40 to 257°F)	-40~125°C (-40~257°F)	-40~125°C (-40~257°F)	-40~125°C (-40~257°F)
	Accuracy	±0.5°C(0~60°C) ±1°C(others)	±0.2°C(10~60°C) ±0.7°C(others)	±0.3°C(0~60°C) ±0.9°C(others)	±0.3°C(0~60°C) ±0.9°C(others)
	Resolution	0.1°C(0.2°F)	0.1°C(0.2°F)	0.1°C(0.2°F)	0.1°C(0.2°F)
Sensor location		External	External	External	External
Readings memory		32,000	32,000	32,000	32,000
Sample rate		1s to 24h	1s to 24h	2s to 24h	2s to 24h
PC software		DGraph software and USB driver required (included in cd)			
Power supply		Rechargeable lithium battery, or power supply via USB interface			
Dimension		120mmX74mmX24mm(4.8"X2.9"X0.9")			
Case material and weight		ABS; Approx. 130 grams(4.59 oz)			

## GSM-10E

SMS / Sound / Light Alarm  
Temperature Data Logger



- A Large LCD Display
- High Reliability and Stability for Industrial-grade Application
  - With External Probe
- Part no.: 1000200050 -
- Probe part no.: 1000700090 -

## GSM-11E

SMS / Sound / Light Alarm Humidity  
and Temperature Data Logger



- A Large LCD Display
- High Reliability and Stability for Industrial-grade Application
  - With External Probe
- Part no.: 1000200048 -
- Probe part no.: 1000700083 -

## GSM-20E

SMS / Sound / Light Alarm Humidity  
and Temperature Data Logger



- A Large LCD Display
- High Reliability and Stability for Industrial-grade Application
  - With External Probe
- Part no.: 1000200046 -
- Probe part no.: 1000700085 -

## GSM-21E

SMS / Sound / Light Alarm Humidity  
and Temperature Data Logger



- A Large LCD Display
- High Reliability and Stability for Industrial-grade Application
  - With External Probe
- Part no.: 1000200044 -
- Probe part no.: 1000700084 -

### Accessories

Part no.

Temperature external probe  
-40~125°C, ±0.5°C



Φ 2.8mm

Φ 4mm

1000700090

2m

87mm

Temperature external probe  
-40~125°C, ±0.2°C



Φ 2.8mm

Φ 4mm

1000700083

2m

87mm

Temperature and humidity external probe  
-40~125°C, ±0.3°C; 0~100%RH, ±3%RH



Φ 2.8mm

Φ 5.8mm

1000700085

3m

21mm

Temperature and humidity external probe  
-40~125°C, ±0.3°C; 0~100%RH, ±2%RH



Φ 2.8mm

Φ 5.8mm

1000700084

3m

21mm