

## HIGH PRECISION DIGITAL INDICATORS

ABSOLUTE ENCODER, THE ORIGINAL  
DATA REMAINS AFTER POWER OFF

Ø28MM STEM SUITABLE FOR  
REINFORCED CLAMPING

DATA  
OUTPUT

LINEAR BALL BEARINGS  
FOR TEN MILLION TIMES USE

ATTENTION: RECHARGEABLE BATTERY,  
FOR 24 HOURS CONTINUOUS WORKING

- Linear ball bearings for ten million times use
- Ø28mm stem suitable for reinforced clamping
- Absolute encoder, the original data remains after power off
- Adjustable resolution: 0.0002mm/0.00001"  
0.001mm/0.00005"  
0.01mm/0.0005"
- Reading in digital and analog
- Button function: data output, tolerance, data preset, data hold, measuring direction change, max./min./TIR, power off time, on/off, mm/inch, adjust resolution
- Power: rechargeable battery, for 24 hours continuous working
- Ruby probe

### With data interface

Optional accessory:  
wireless transmitter, code **7315-60**, wireless receiver, code **7315-2**, **7315-3**  
data output cable (keyboard format), code **7302-60**  
data output cable (serial port format), code **7305-G60**  
(cable length 3m, optional cable length maximum 15m; RS232 protocol, optional RS485 protocol)

Code	Range	Accuracy	Hysteresis	Remark
2140-6	0-6mm/0-0.24"	1.6µm	0.8µm	flat back



### Built-in wireless

Optional accessory:  
wireless receiver (keyboard format), code **2134-R1**  
wireless receiver (serial port format), code **2134-R2**

Code	Range	Accuracy	Hysteresis	Remark
2140-6WL	0-6mm/0-0.24"	1.6µm	0.8µm	flat back




2140-6



wireless receiver  
2134-R1, 2134-R2 (optional)



warning when  
over tolerance



analog pointer

