









BS-2036F(LED) Fluorescent Biological Microscope



Introduction

BS-2036F(LED) Series LED fluorescence microscopes are newly developed microscopes, the microscopes use LED as the light source, the life span of the LED lamp is much longer than mercury lamp. It has 6 turret positions for filter cubes, more filter cubes can be used together.

Features

- 1. Excellent fluorescent image with infinite optical system.
- 2. LED illumination with 50,000 hours life span.
- 3. Convenient to use, no need warm-up.
- 4. No need for cooling due to LED cold light source.
- 5. 6 positions for filter cubes.

Application

BS-2036F(LED) series LED Fluorescence microscopes are used to study the absorbing, transportation, chemicals distribution and positioning in cells. They are widely used in disease examination, immune diagnosis and life science areas.

Specifications

Item	Specification		BS-2036
			FT(LED)
Optical System	Infinite Optical System	•	•
Viewing Head	Seidentopf Binocular Viewing Head, Inclined at 30°, 360° Rotatable, Interpupillary		
	48-75mm	•	
	Seidentopf Trinocular Viewing Head, Inclined at 30°, 360° Rotatable, Interpupillary		
	48-75mm, Light Distribution: 20:80 (eyepiece: trinocular tube)		•

















Eyepiece	WF10×/20mm				•	•
	WF16×/13mm				0	0
	Reticule Eyepiece WF10×/20mm (0.1mm)				0	0
Objective	Infinite E-Plan Achromatic Objective 4×, 10×, 40×, 100×(Oil)				•	•
	Infinite Plan Achromatic Objective 4×, 10×, 20×, 40× (S), 60× (S), 100× (Oil) (S)				0	0
Nosepiece	Backward Quadruple Nosepiece				•	•
	Backward Quintuple Nosepiece					0
Focusing	Coaxial Coarse & Fine Focusing knobs, Travel Range: 26mm, Scale:2um					•
Stage	Stage Size: 145×140mm, Cross Travel 76×52mm, Two Slide Holder				•	•
	Rackless Double Layers Mechanical Stage, Size: 140×135mm, Cross Travel					0
	75×35mm, Scale 0.1mm, Two Slide Holder				ļ	
Condenser	Abbe Condenser NA1.25 with Iris Diaphragm					•
Transmitted Illumination	3W-LED Illumination Systems, Brightness Adjustable				•	•
	6V/20W Halogen Lamp, Brightness Adjustable					
	6V/30W Halogen Lamp, Brightness Adjustable				0	0
Optional	Field Diaphragm, Photo adapters(for DSLR cameras), Video adapters(1X, 0.5X),					0
Accessories	Polarization set, Phase of	0				
Reflected Light Source		Excitation	Dichroic Mirror	Barrier Filter		
	Blue excitation	420-490	505	520	•	•
	Green excitation	500-550	575	590	•	•
	Uv excitation	330-380	400	435	0	0
	V excitation	380-420	430	460	0	0
Fluorescent Lamp	5W LED Lamp	•	•			
Package	42cm*28cm*45cm, 40c	•	•			

Note: ●Standard Outfit, oOptional

Sample Images









