

Vertical Pulse Vacuum Steam Sterilizer

Pulse vacuum automatic



Use:

The vertical pressure steam sterilizers are assembled with heating system, micro-computer controlled system, over heat and over pressure protection system, which are reliable for the sterilizing effects, convenient of operation and energy conservation. They are ideal equipments for clinics, scientific research institutes and other organizations to sterilize surgical instruments, fabrics, glasses, culture media etc.

Characteristics:

- * Micro computer controlled, digital display of working status, touch type key.
- * It dynamically shows the temperature, pressure time, vacuum rate and the cycle status.
- * With fully automatically route of the water inlet, pulse vacuum, heating, sterilizing, draining, exhausting and vacuum drying.
- * 3 times pulse vacuum, the vacuum rate reach 0.081 mpa after that, which ensure the completely extracting of inner air from the dressing and A.B. type hollowed appliance.
- * With 4 fixed programs for the appliance, medical dressing, rubber and fluid, the user also could set the program as they need randomly.
- * Equipped with the PY/TT testing connector, easy for running the testing.
- * Multiple pulse vacuum drying after sterilizing, which ensure the good sterilizing result.
- * Equipped with 0.22µm bacteria filter, it ensure the air which enter the inner vacuum chamber is sterile, avoid the second time contamination.
- * Hand wheel type for quick-open the door. Self-inflating type seal.
- * Adopted with immersed heating tube, with high heating efficiency.
- * Steam-water inner circulation system: no steam discharge, and the environment for the sterilizing will be clean and dry.
- * Automatically shut off with beep reminding after sterilizing will be clean and dry.
- * Automatically shut off with beep reminding after sterilization.
- * Fully high quality stainless, equipped with double stainless steel basket.

Technical Data

MODEL	LS-50HV	LS-75HV	LS-100HV
Technical Data			
Chamber volume	50L φ340x550mm	75L φ400x600mm	100L φ440x650mm
Working Pressure	0.22Mpa		
Working temperature	134°C		
Max. working pressure	0.23Mpa		
Heat average	≤ ± 1°C		
Timer range	0-99min or 0-99hour59min		
Temperature adjust range	0-134°C		
Power	3000W/AC220V 50Hz	4500W/AC220V 50Hz	4500W/AC220V 50Hz
Overall dimension	690 x 470 x 1140	730 x 510 x 1270	750 x 550 x 1305
Transport dimension	760 x 550 x 1290	820 x 600 x 1380	840 x 640 x 1410
G.W / N.W	120Kg / 100Kg	140Kg / 118kg	160Kg / 128Kg