

SEALING MACHINE SERIES

封口机系列



FR770 连续式封口机
CONTINUOUS SEALING MACHINE



FR900 连续式封口机
CONTINUOUS SEALING MACHINE



FR-1000 连续封口机
CONTINUOUS SEALING MACHINE

性能及特点 / Performance and Features

本机采用电子恒温控制装置和无级调速的传动机构，可封制各种不同材料的塑料薄膜袋，也可与各种包装流水线配套使用，其封口长度不受限制。本机具有连续封口效率高、封口质量可靠、结构合理、操作方便等特点。连续封口机种类齐全，不但有立式、落地式、左进料、不锈钢机箱等，更有双加热、封口加宽、封口加深、封口与输送台距离加高，智能表控制、封口宽度3MM等机型可定制。

This machine adopts electronic constant temperature control device and stepless speed regulation transmission mechanism, which can seal various plastic film bags of different materials, and can also be matched with various packaging lines. For sleeve use, the sealing length is not limited. This machine has continuous sealing efficiency, reliable sealing quality, reasonable structure, and convenient operation. Continuous sealing machine varieties are complete, not only vertical, floor-standing, left-feeding, stainless steel chassis, etc., more double heating, wider sealing, deeper sealing, longer distance between sealing and conveyor. High, smart meter control, sealing width 3MM and other models can be customized.

技术参数 / Technical Parameters

型号	Model	FR-770	FR-900	FR1000
电源电压(V/Hz)	Voltage	220V 50Hz	220V 50Hz	220V 50Hz
加热功率(W)	Heating Power	500	500	600
封口速度(m/min)	Sealing Speed	0-16	0-24	0-16
封口宽度(mm)	Sealing Width	15	15	14
温控范围(°C)	Temperature Control	0-400	0-300	0-400
封口厚度(mm)	Sealing Thickness	0.02-0.80	0.02-0.80	0.02-0.80
印字个数(Pcs)	Number of Printing	≤39	≤39	≤19
输送载荷(Kg)	Transport Load	≤5	≤5	≤10
电机功率(W)	Motor Power	80	80	120
外型尺寸(mm)	Dimensions	895x420x345	895x420x345	950x400x300
整机重量(Kg)	Total Weight	22	20	28

SEALING MACHINE SERIES 封口机系列



FR-770-250型多功能薄膜封口机
MULTIFUNCTIONAL FILM SEALING MACHINE

技术参数 / Technical Parameters

型号	Model	FR-770-250
电源电压(V/HZ)	Voltage	220V 50Hz
加热功率(W)	Heating Power	600
封口速度(m/min)	Sealing Speed	0-24
封口宽度(mm)	Sealing Width	12
温控范围(°C)	Temperature Control	0-400
封口厚度(mm)	Sealing Thickness	0.02-0.80
印字个数(Pcs)	Number of Printing	W39
输送载荷(Kg)	Transport Load	W10
输送台宽度(mm)	Conveyor Width	250
电机功率(W)	Motor Power	100
外型尺寸(mm)	Dimensions	1100x510x320
整机重量(Kg)	Total Weight	30



FR-770-300型多功能薄膜封口机
MULTIFUNCTIONAL FILM SEALING MACHINE

技术参数 / Technical Parameters

型号	Model	FR-770-300
电源电压(V/HZ)	Voltage	220V 50Hz
加热功率(W)	Heating Power	600
封口速度(m/min)	Sealing Speed	0-24
封口宽度(mm)	Sealing Width	12
温控范围(°C)	Temperature Control	0-400
封口厚度(mm)	Sealing Thickness	0.02-0.80
印字个数(Pcs)	Number of Printing	W39
输送载荷(Kg)	Transport Load	W10
输送台宽度(mm)	Conveyor Width	400
电机功率(W)	Motor Power	100
外型尺寸(mm)	Dimensions	1100x640x320
整机重量(Kg)	Total Weight	32



FR-770F型立式薄膜封口机
VERTICAL FILM SEALING MACHINE

技术参数 / Technical Parameters

型号	Model	FR-770立式
电源电压(V/HZ)	Voltage	220V 50Hz
加热功率(W)	Heating Power	500
封口速度(m/min)	Sealing Speed	0-16
封口宽度(mm)	Sealing Width	15
温控范围(°C)	Temperature Control	0-400
封口厚度(mm)	Sealing Thickness	0.02-0.80
印字个数(Pcs)	Number of Printing	W39
输送载荷(Kg)	Transport Load	W5
电机功率(W)	Motor Power	80
外型尺寸(mm)	Dimensions	895x420x345
整机重量(Kg)	Total Weight	22

SEALING MACHINE SERIES 封口机系列



FR-450 立式封口机
VERTICAL SEALING MACHINE



不锈钢
Stainless steel



喷漆
Spray paint

FR-770F 立式封口机
VERTICAL SEALING MACHINE

技术参数 / Technical Parameters

型号	Model	FR-450	FR770F
电源电压(V/Hz)	Voltage	220V 50Hz	220V 50Hz
加热功率(W)	Heating Power	600	500
封口速度(m/min)	Sealing Speed	0-24	0-16
封口宽度(mm)	Sealing Width	12	15
温控范围(°C)	Temperature Control	0-400	0-400
封口厚度(mm)	Sealing Thickness	0.02-0.80	0.02-0.80
印字个数(Pcs)	Number of Printing	W39	W39
输送载荷(Kg)	Transport Load	W15	W5
输送台宽度(mm)	Conveyor Width	250	250
电机功率(W)	Motor Power	120	80
高度(mm)	Height	220-500	220-500
外型尺寸(mm)	Dimensions	1100x550x590	895x420x345
整机重量(Kg)	Total Weight	40	22



手钳式封口机
PLIERS TYPE SEALING MACHINE

型号	Model	FKR-200	FKR-300	FKR-400
电压(V/Hz)	Voltage	110/220V	110/220V	110/220V
功率(W)	Power	300	400	500
封口长度(mm)	Sealing Length	200	300	400
包装尺寸(mm)	Package Dimensions	440x310x155	440x310x155	440x310x155
重量(Kg)	Temperature Control	1.115	1.295	1.405
温度(°C)	Temperature	0-300°C	0-300°C	0-300°C

SEALING MACHINE SERIES

封口机系列



手压封口机
BODY SEALING MACHINE

性能及特点 / Performance and Features

- ◆ 本机是完美的塑料袋封接机，可以很方便的用来封装各种糖果食品、一般商品、文具及药品等。
- ◆ SF塑-100/200/250/300/400型使用安全不漏电，可广泛用于封口，价格实惠耐用，是家庭商店必备之理想封口设备。
- ◆ This is a perfect plastic-bag sealer and can be easily used to seal for various sweets, foods, general merchandises, stationeries and medic-ines.
- ◆ Hand-press SF plastic-100/200/250/300/400 is save without leakage and can be extensively used, economical, an ideal sealer necessary for families and shops.

型号	Model	SF-100	SF-200	SF-250	SF-300	SF-400	SF-200typing	SF-300typing
脉冲功率(w)	Impulse Power	200	300	350	400	600	500	600
最大封接长度(mm)	Max.sealing Length	100	200	250	300	400	200	300
最大封接厚度(mm)	Max.seal Thickness	0.2	0.3	0.356	0.4	0.6	0.8	0.8
最大封接宽度(mm)	Max.sealing Width	2	2	2.5	3	3	8	8-10
加热时间(s)	Heat Time	0.1-1.5	0.2-1.5	0.2-1.5	0.2-1.5	0.2-2	0.2-2	0.2-2
重量(kg)	Machine Weight	1.8	2.7	3	3.5	4	3	3.5
尺寸(cm)	Machine Size	24x9x16	8x32x15	8x37x15	8.5x45x18	54x9x18	8x32x15	8.5x45x18



脚踏式封口机系列
Foot sealing machine series

型号 Model	瞬间功率(w) Instantaneous Power	气源压力(MPa) Air Pressure	封口长度(mm) Sealing Length	封口宽度(mm) Sealing Width	封口厚度(mm) Sealing Thickness	加热时间(sec.) Heating Time	冷却时间(sec.) Cooling Time	自动时间(sec.) Automatic Time	重量(kg) Weight
QCH-350	1050	0.4-0.6	350						18
QCH-450	1250	0.4-0.6	450						19
QCH-500	1350	0.4-0.6	500	2-8	0.4	0.2-3	1-8	1-8	20
QCH-600	1450	0.4-0.6	600						22
QCH-650	1550	0.4-0.6	650						23

型号 Model	瞬间功率(w) Instantaneous Power	最大长度(mm) Max.seal Length	封口宽度(mm) Sealing Width	最大密封(mm) Max Seal	加热时间(sec.) Heating Time	冷却时间(sec.) Cooling Time	重置时间(sec.) Reset time	重量(kg) Weight	外形尺寸(cm) Dimensions
PFS-A450	1200	450						20	52x37x21
PFS-A650	1500	650						22	73x37x21
PFS-A450x2	1800	450	2-8	0.4	0.2-3	1-8	1-8	21	52x37x21
PFS-A650x2	2050	650						23	73x37x21

型号 Model	瞬间功率(w) Instantaneous power	封口长度(mm) Sealing length	封口宽度(mm) Sealing width	封口厚度(mm) Sealing thickness	加热时间(sec.) Heating time	重量(kg) Weight
PFS-F350	1000	350				18
PFS-F450	1200	450				19
PFS-F500	1300	500				20
PFS-F600	1400	600	2-8	0.4	0.2-3	22
PFS-F650	1500	650				23
PFS-F800	1800	800				25