

MAGNETIC PUMP FILLING MACHINE SERIES

磁力泵灌装机系列



GFK-280 定量灌装机(单头)
FILLING MACHINE(SINGLE HEAD)



GFK-280 定量灌装机(双头)
FILLING MACHINE(DOUBLE HEAD)



GFK-160 电动数控液体灌装机
ELECTRIC CNC LIQUID FILLING MACHINE



GFK-1700 液体灌装机
LIQUID FILLING MACHINE



GFK-3500 液体灌装机
LIQUID FILLING MACHINE

性能及特点 / Performance and Features

- ◆ 进口单片电机控制，不锈钢外壳，复合GMP要求。
- ◆ LCD液晶显示屏，面板操作更加方便简单。
- ◆ 出料嘴防滴漏设计，灌装精度高，计量准确。
- ◆ 自动进行计数功能，有效控制灌装数量。
- ◆ Imported single-chip motor control, stainless steel housing, composite GMP requirements.
- ◆ LCD liquid crystal display, panel operation more convenient and simple.
- ◆ Outlet nozzle anti-drip design, filling high precision, accurate measurement.
- ◆ Automatic counting function, effective control of the number of filling.

技术参数 / Technical Parameters

型号	Model	GFK-280单头	GFK-280双头	GFK-160	GFK-1700	GFK-3500
电源	Power Supply	AC 220V/±5%	AC 220V/±5%	AC 220V/±5%	AC 220V/50Hz	AC 220V/50Hz
功率(W)	Power	30	60	30	480	830
最大范围(ml)	Maximum Range	5-3500	5-3500	5-3500	20-17000	50-35000
最大吸程(m)	Maximum Suction Range		2		2	2
最大流量(L/min)	Maximum Flow		3.2		17	35
重复误差	Repeat the Error		<0.5%			±1%
防滴漏功能	Anti-drip Function		YES			YES
断电记忆功能	Power off Memory Function		YES			YES
整机重量(Kg)	Total Weight	4.5	8.5	5.5	13	15

MAGNETIC PUMP FILLING MACHINE SERIES

磁力泵灌装机系列



SY-1 磁力泵液体灌装机
MAGNETIC PUMP LIQUID FILLING MACHINE



SY-2 磁力泵液体灌装机
MAGNETIC PUMP LIQUID FILLING MACHINE

性能及特点 / Performance and Features

- ◆ 齿轮泵头靠磁力驱动，泵头与电机无轴连接，不用担心轴封损坏泄露或者泵的负载过高而烧坏电机；泵头及电机选用德国进口，其他元件均为台湾生产，性能稳定可靠，使用寿命长，泵头为316不锈钢材质，耐酸碱，耐腐蚀；灌装时间精确到0.01秒从而确保灌装精确，误差小于1.5%；灌装量5ml-无限量可调；功能齐全，可手动脚踏间歇灌装，也可自动间歇灌装，间歇时间可调；使用范围广泛。
- ◆ Gear pump head by magnetic force, the pump head and the motor without shaft connection, do not worry about the shaft seal damage or pump load is too high and burn the motor; pump head and motor selection of German imports, other components are produced in Taiwan, stable and reliable performance, The service life is long, the pump head is 316 stainless steel, acid and alkali resistance, corrosion resistance; filling time is accurate to 0.01 seconds to ensure accurate filling, the error is less than 1.5%; filling volume 5ml- unlimited adjustable; Manual intermittent filling can also be intermittent filling, intermittent time adjustable; use a wide range.

技术参数 / Technical Parameters

型号	Model	SY-1	SY-2
电压	Voltage	220V/ ± 5%	220V/ ± 5%
最大功率(w)	Maximum Power	40	80
主机重量(kg)	Host Weight	14	18
灌装误差	Filling Error	± 1.5%	
最大流量(单泵)	Maximum Flow (Single Pump)	3L/min	
主机尺寸(mm)	Host Size (mm)	410x330x270	510x330x270
包装尺寸(mm)	Packing Size (mm)	600x470x365	600x470x365